

Country of Origin : China  
 Efficiency level (ErP) : VI



**GREEN MODE**      **RoHS**


**Specifications**

Model	Output port usage	Output Specification	Max Power (W)
SYS1102 W2E	Type C1	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A 3.3-21V/3A (65W max)	65
	Type C2	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A 3.3-21V/3A (65W max)	65
	Type A	5V/3A, 9V/2A, 12V/1.5A (18W max)	18
	Type C1+C2	C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A 5.0-21V/2.1A (45W max) + C2: 5V/3A, 9V/2.22A, 12V/1.66A (20W max)	65
	Type C1+A	C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A 5.0-21V/2.1A (45W max) + A: 5V/3A, 9V/2A, 12V/1.5A (18W max)	63
	Type C2+A	C2+A: 5V/3A (15W max)	15
	Type C1+C2+A	C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A 5.0-21V/2.1A (45W max)+ C2+A: 5V/3A (15W max)	60

**Features:**

GaN technology Power Supply  
 Auto-detect the charging voltage and current for Type C and ios devices  
 Support PD3.0 | QC3.0 | PPS protocols  
 PSU housing W2E - Europe  
 Output connector: Regulated Output With Low Ripple Noise | Safety Agency Requirements and EMI/EMS Certified  
 Private Label Marking Available | 2 Years Warranty

INPUT   OUTPUT	Voltage	90-264VAC
	Current	2.0A rms max   At AC low line input and DC output full load
	Power consumption	0.21W max. with output no load at 115VAC/230VAC input
	Efficiency	Meet ERP level VI
	Turn delay	3000mS max.   3S max on the condition that input volotage 230V, full load
	Ripple noise	300mV
	Burn-in	2 Hour Full Load
PROTECTION	Over current Short protection	Fold back
	Input protection	3.15A/250V Fuse   The power supply shall be protected against power line surges and any abnormal condition
	Protection class	Class II
SAFETY	CE EMC	2014/30/EU
	CE LVD	2014/35/EU EN IEC 62368-1
	Safety approvals	CE
	Dielectric Strength (Hi-pot)	IEC 320 2pin primary to secondary 4000Vdc 10mA 1min
	Leakage current	0.25 mA max.
ENVIRONMENTAL	Temperature	Operating: 0~35°C / Storage: -20~85°C
	Humidity	Operating: 8%~90%RH / Storage:5%~95% RH
	Cooling	Natural Convection Cooling
OTHER	MTBF	MTBF shall be least 50,000 hours at 25°C (MIL-HDBK-217F)
	Weight	111g
	Dimension	78x28x46 mm
	Packing	80 pcs   1 box

Mechanical case specification:

